

PremARC™ 60-80

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PremARC™ 60-80
Material Type: Isocyanate
Manufacturer/Supplier: American Recycling Center, Inc.
655 Wabassee Drive
Owosso, MI 48867

24-Hour Emergency Phone Number: 800-424-9300
Customer Information Center: 989-725-5100

2. HAZARDS IDENTIFICATION

Emergency Overview

Color: Red to Brown

Physical State: Liquid

Odor: Characteristic

Hazards of Product:

WARNING! May cause allergic skin reaction. May cause allergic respiratory reaction. May cause eye irritation. May cause skin irritation. Sprayed or heated material harmful if inhaled. May cause respiratory tract irritation. May cause lung injury. May react with water. Isolate area. Keep upwind of spill. Stay out of low areas. Slipping hazard. Elevated temperatures can cause hazardous polymerization. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction. Toxic fumes may be released in fire situations.

OSHA Hazard Communication Standard

This Product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Health Effects

Eye Contact: May cause eye irritation. May cause slight temporary corneal injury.

Skin Contact: Prolonged contact may cause skin irritation with local redness. Material may stick to skin causing irritation upon removal. May stain skin.

Skin Absorption: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Skin Sensitization: Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

Inhalation: At room temperature, vapors are minimal due to low volatility. However, certain operations may generate vapor or mist concentrations sufficient to cause respiratory irritation and other adverse effects. Such operations include those in which the material is heated, sprayed or otherwise mechanically dispersed such as drumming, venting or pumping. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs).



American Recycling Center, Inc

655 Wabassee Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Effects may be delayed. Decreased lung function has been associated with overexposure to isocyanates.

Respiratory Sensitization: May cause allergic respiratory response. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

Ingestion: Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Observations in animals include: Gastrointestinal irritation.

Effects of Repeated Exposure: Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

Cancer information: Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

Birth Defects/Developmental Effects: In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother.

3. COMPOSITION INFORMATION

Component	CAS #	Amount
Polymethylenepolyphenyl polyisocyanate, Polyporpyleneglycol copolymer	53862-89-8	>60.0 - <90.0%
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	>10.0 - <30.0%
4,4'-Methylenediphenyl diisocyanate	101-68-8	>7.0 - <13.0%

Note: CAS 101-68-8 is an MDI isomer that is part of CAS 9016-87-9.

4. FIRST AID MEASURES

Eye Contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist.

Skin Contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. An MDI skin decontamination study demonstrated that cleaning very soon after exposure is important, and that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Notes to Physician: Maintain adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. Treatment of exposure should be directed at the control of symptoms and the clinical conditions of the patient.



American Recycling Center, Inc

655 Wabasse Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Medical Conditions Aggravated by Exposure: Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

5. FIRE-FIGHTING MEASURES

Extinguishing Media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Do not use direct water stream. May spread fire. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gasses (fumes) can accumulate. Water is not recommended, but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire affected zone until fire is out. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

Unusual Fire and Explosion Hazards: Product reacts with water. Reaction may produce heat and/or gases. This reaction may be violent. Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Isocyanates. Hydrogen cyanide. Carbon monoxide, Carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Steps to be Taken if Material is Released or Spilled: Contain spilled material if possible. Absorb with materials such as: Vermiculite. Dirt. Sand. Clay. Do NOT use absorbent materials such as: Cement powder (Note: may generate heat). Collect in suitable and properly labeled open containers. Do not place in sealed containers. Suitable containers include: Metal drums. Plastic drums. Polylined fiber pacs. Wash the spill site with large quantities of water. Attempt to neutralize by adding suitable decontaminant solution: Formulation 1: sodium carbonate 5 – 10%; liquid detergent 0.2 – 2%; water to make up 100%, OR Formulation 2: concentrated ammonia solution 3 – 8%; liquid detergent 0.2 – 2%; water to make up 100%. If ammonia is used, use good ventilation to prevent vapor exposure. See section 13, Disposal Considerations, for additional information.



American Recycling Center, Inc

655 Wabasse Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Continued on Next Page...

Personal Precautions: Isolate area. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. Keep unnecessary and unprotected personnel from entering the area. If available, use foam to smother or suppress. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. See Section 10 for more specific information.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. HANDLING AND STORAGE

Handling

General Handling: Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid breathing vapor. Wash thoroughly after handling. Use with adequate ventilation. Keep container closed. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Other Precautions: Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Storage

Store in a dry place. Protect from atmospheric moisture. Do not store product contaminated with water to prevent potential hazardous reaction. See Section 10 for more specific information. Additional storage and handling information on this product may be obtained by calling your sales or customer service contact.

Shelf life: Use within
6 Months

Storage temperature:
24 – 41° C

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Exposure Limits

Component	List	Type	Value
4,4'-Methylenediphenyl diisocyanate	ACGIH	TWA	0.005 ppm
	OSHA Table Z-1	Ceiling	0.2 mg/m ³ 0.02 ppm

Personal Protection

Eye/Face Protection: Use chemical goggles. Eye wash fountain should be located in immediate work area.

Skin Protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. Remove contaminated clothing immediately, wash skin area with soap and water, and launder clothing before reuse or dispose of properly. Items which cannot be decontaminated, such as shoes, belts, and watchbands, should be removed and disposed of properly.



American Recycling Center, Inc

655 Wabasse Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Hand Protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials as well as the instructions/specifications provided by the glove supplier.

Respiratory Protection: Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved air-purifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus of positive pressure air line with auxiliary self contained air supply. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Color	Red to Brown
Odor	Characteristic
Flash Point – Closed Cup	>150°C (>302°F) <i>Estimated</i>
Flammability (solid, gas)	Not applicable to liquids
Flammable Limits in Air	Lower: No test data available Upper: No test data available
Autoignition Temperature	No test data available
Vapor Pressure	<0.00001 mmHg @ 25° C <i>Literature</i>
Boiling Point (760 mmHg)	>100°C (>212°F) <i>Literature</i>
Vapor Density (air = 1)	No test data available
Specific Gravity (H2O = 1)	1.09 ASTM D891
Freezing Point	No test data available
Melting Point	No test data available
Solubility in water (by Weight)	<i>Literature</i> insoluble, reacts, evolution of CO2
pH	<i>Literature</i>
Decomposition Temperature	No test data available



American Recycling Center, Inc

655 Wabasse Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Partition coefficient, n-octanol/water(log Pow)	No test data available for this product.
Evaporation Rate (Butyl Acetate =1)	No test data available
Kinematic Viscosity	2,500 cSt @ 25°C <i>ASTM D4878</i>

10. STABILITY AND REACTIVITY

Stability/Instability

Stable under recommended storage conditions. See Storage, Section 7.

Conditions to Avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid. Avoid moisture. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction.

Incompatible Materials: Avoid contact with: Acids. Alcohols. Amines. Water. Ammonia. Bases. Metal compounds. Moist air. Strong oxidizers. Products based on diisocyanates like TDI and MDI react with many materials to release heat. The reaction rate increases with temperature as well as with increased contact; these reactions can become violent. Contact is increased by stirring or if the other materials acts as a solvent. Products based on diisocyanates such as TDI and MDI are not soluble in water and will sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Avoid contact with metals such as: Aluminum. Zinc. Brass. Tin. Copper. Galvanized metals. Avoid unintended contact with polyols. The reaction of polyols and isocyanates generate heat.

Hazardous Polymerization

Can occur. Polymerization can be catalyzed by: Strong bases. Water.

Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials. Gases are released during decomposition.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Ingestion

Single dose oral LD50 has not been determined. Estimated LD50, Rat >2,000 mg/kg

Skin Absorption

The dermal LD50 has not been determined. Estimated LD50, Rabbit >2,000 mg/kg

Sensitization

Skin

Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.



American Recycling Center, Inc

655 Wabassee Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Respiratory

May cause allergic respiratory response. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

Repeated Dose Toxicity

Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

Chronic Toxicity and Carcinogenicity

Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

Developmental Toxicity

In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother.

Reproductive Toxicity

No relevant information found.

Genetic Toxicology

In vitro genetic toxicity studies were negative for component(s) tested. Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE

Movement & Partitioning

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Persistence and Degradability

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Ecotoxicity

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 > 100 mg/L in the most sensitive species tested).

Toxicity to Soil Dwelling Organisms

LC50, Earthworm *Eisenia foetida*, adult, 14 d: > 1,000 mg/kg

13. DISPOSAL CONSIDERATIONS

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE



American Recycling Center, Inc

655 Wabasse Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Continued on Next Page...

MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler, Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

14. TRANSPORT INFORMATION

DOT Non-Bulk
NOT REGULATED

DOT Bulk
Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S
Technical Name: MDI
Hazard Class: 9 **ID Number:** UN3082 **Packing Group:** PG III

IMDG
NOT REGULATED

ICAO/IATA
NOT REGULATED

Additional Information

Reportable quantity: 38,462 lb – MDI

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes
Delayed (Chronic) Health Hazard	Yes
Fire Hazard	No
Reactive Hazard	Yes
Sudden Release of Pressure Hazard	No



American Recycling Center, Inc

655 Wabasse Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Superfund Amendments and Regulation Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product contains the following substances which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372.

Component	CAS #	Amount
4,4'-Methylenediphenyl diisocyanate	101-68-8	>7.0 - <13.0%
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	>10.0 - <30.0%

Pennsylvania (Worker and Community Right-to-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Component	CAS #	Amount
4,4'-Methylenediphenyl diisocyanate	101-68-8	>7.0 - <13.0%

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substance known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CEPA – Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. OTHER INFORMATION

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact.

Recommended Uses and Restrictions

Component(s) for the manufacture of urethane polymers. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

Revision

Identification Number: 1010572 / 1001 / Version 2.0



American Recycling Center, Inc

655 Wabasse Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com

Legend

N/A	Not Available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
WEEL	Workplace Environmental Exposure Level
HAZ-DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

American Recycling Center, Inc. urges each customer or recipient of the (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in the (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, expressed or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

Issue Date: 03/27/2009

Print Date: 03/24/2010

PremARC™ 60-80

The information herein is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. We request that customers inspect and test our products before use and satisfy themselves as to contents and suitability. We warrant that our products will meet our written specifications. Nothing herein shall constitute and other warranty express or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for special, incidental or consequential damages.



American Recycling Center, Inc

655 Wabassee Drive, Owosso, MI 48867
(989) 725-5100 www.americanrecycling.com